



- NOTES:
 1. PIPING MATERIAL: HDPE
 2. CONNECTION TYPE: ISO1.0mpa FLANGE.
 3. MANUAL VALVES SHALL BE INSTALLED AT THE INLET AND OUTLET OF THE DISC FILTER.
 4. THE DRAIN PIPE SHALL BE CONNECTED TO THE DRAINAGE SYSTEM.
 5. POWER SUPPLY: 220V/1PHASE/50HZ.
 6. CONCRETE FOUNDATION (HEIGHT: 200MM)
 7. AND EXPANSION ANCHOR BOLTS ARE SUGGESTED FOR SITE INSTALLATION.

9	Inlet Pipe 6"	1		
8	Drain Pipe 3"	1		
7	Outlet Pipe 6"	1		
6	HF-K-1.0 Controller	1		
5	Couplings	28	Carbon steel st	
4	Water Source Filter	1	Reinforced Polyamide	
3	Pressure Gauge	2	SS304	
2	Backwash Valve	7	Reinforced Polyamide	
1	Disc Filter Unit	7	Reinforced Polyamide	
NO.	Description	Quantity	Spec. & Material	Weight

		Beijing Haiiao Technologies Co.,Ltd			
标记	处数	分区	更改文件号	签名	DATE
R	内部评审版				
A	初步设计				
REV	DESCRIPTION	DESD	DATE	APPD	DATE
		HF-A2-7-6 DISCFILTER		MATERIAL	QUANTITY
		HF-A-02-7-00-01		WEIGHT	SCALE
				1	1:1
				SHEET	OF