



- NOTES:
 1. PIPING MATERIAL: PE, Carbon steel st, 304.
 2. CONNECTION TYPE: ANSI 150# FLANGE.
 3. MANUAL VALVES SHALL BE INSTALLED AT THE INLET AND OUTLET OF THE DISC FILTER.
 4. THE DRAIN PIPE SHALL BE CONNECTED TO THE DRAINAGE SYSTEM.
 5. POWER SUPPLY: 220V/1PHASE/50HZ.
 6. CONCRETE FOUNDATION (HEIGHT: 200MM)
 7. AND EXPANSION ANCHOR BOLTS ARE SUGGESTED FOR SITE INSTALLATION.

9	Inlet Pipe 8"	1		
8	Drain Pipe 3"	1		
7	Outlet Pipe 8"	1		
6	HF-K1.0 Controller	1		
5	Couplings	48	Carbon steel st	
4	Water Source Filter	1	Reinforced Polyamide	
3	Pressure Gauge	2		
2	Backwash Valve	12	Reinforced Polyamide	
1	Disc Filter Unit	12	Reinforced Polyamide	
NO.	Description	Quantity	Spec. & Material	Weight

							Beijing HaiAo Technologies Co.,Ltd			
标记	处数	分区	更改文件号	签名	DATE	HF-A3-12-8 DISCFILTER	MATERIAL	QUANTITY	WEIGHT	SCALE
R	内部评审版					FIG NO	/	1		1:1
A	初步设计					HF-A03-12-00-01				
REV	DESCRIPTION	DESD	DATE	APPD	DATE	APPI	DATE	SHEET OF		